


PATENT COOPERATION TREATY



PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)



Applicant's or agent's file reference -	FOR FURTHER ACTION See Form PCT/PEA/416	
International application No. PCT/IS2004/000019	International filing date (day/month/year) 12.11.2004	Priority date (day/month/year) 14.11.2003
International Patent Classification (IPC) or national classification and IPC G01G19/30, B07C5/18		
Applicant MAREL HF. et al.		
<p>1. This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.</p> <p>2. This REPORT consists of a total of 6 sheets, including this cover sheet.</p> <p>3. This report is also accompanied by ANNEXES, comprising:</p> <p>a. <input checked="" type="checkbox"/> sent to the applicant and to the International Bureau a total of 17 sheets, as follows:</p> <p><input checked="" type="checkbox"/> sheets of the description, claims and/or drawings which have been amended and are the basis of this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).</p> <p><input type="checkbox"/> sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the Supplemental Box.</p> <p>b. <input type="checkbox"/> (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)) , containing a sequence listing and/or tables related thereto, in computer readable form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).</p>		
<p>4. This report contains indications relating to the following items:</p> <p><input checked="" type="checkbox"/> Box No. I Basis of the opinion</p> <p><input type="checkbox"/> Box No. II Priority</p> <p><input type="checkbox"/> Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability</p> <p><input type="checkbox"/> Box No. IV Lack of unity of invention</p> <p><input checked="" type="checkbox"/> Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement</p> <p><input type="checkbox"/> Box No. VI Certain documents cited</p> <p><input type="checkbox"/> Box No. VII Certain defects in the international application</p> <p><input type="checkbox"/> Box No. VIII Certain observations on the international application</p>		
Date of submission of the demand 14.09.2005	Date of completion of this report 16.02.2006	
Name and mailing address of the international preliminary examining authority:  European Patent Office - P.B. 5818 Patentlaan 2 NL-2280 HV Rijswijk - Pays Bas Tel. +31 70 340 - 2040 Tx: 31 651 epo nl Fax: +31 70 340 - 3016	Authorized Officer Ganci, P Telephone No. +31 70 340-3384 	

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.
PCT/IS2004/000019

Box No. 1 Basis of the report

1. With regard to the **language**, this report is based on the international application in the language in which it was filed, unless otherwise indicated under this item.
- ☐ This report is based on translations from the original language into the following language , which is the language of a translation furnished for the purposes of:
- ☐ international search (under Rules 12.3 and 23.1(b))
- ☐ publication of the international application (under Rule 12.4)
- ☐ international preliminary examination (under Rules 55.2 and/or 55.3)
2. With regard to the **elements*** of the international application, this report is based on *(replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report)*:

Description, Pages

1-13 filed with telefax on 20.01.2006

Claims, Numbers

1-21 filed with telefax on 20.01.2006

Drawings, Sheets

1/10-10/10 as originally filed

- ☐ a sequence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing
3. ☐ The amendments have resulted in the cancellation of:
- ☐ the description, pages
 - ☐ the claims, Nos.
 - ☐ the drawings, sheets/figs
 - ☐ the sequence listing (*specify*):
 - ☐ any table(s) related to sequence listing (*specify*):
4. ☐ This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).
- ☐ the description, pages
 - ☐ the claims, Nos.
 - ☐ the drawings, sheets/figs
 - ☐ the sequence listing (*specify*):
 - ☐ any table(s) related to sequence listing (*specify*):

* If item 4 applies, some or all of these sheets may be marked "superseded."

**INTERNATIONAL PRELIMINARY REPORT
ON PATENTABILITY**

International application No.
PCT/IS2004/000019

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Yes: Claims	1-21
	No: Claims	
Inventive step (IS)	Yes: Claims	1-21
	No: Claims	
Industrial applicability (IA)	Yes: Claims	1-21
	No: Claims	

2. Citations and explanations (Rule 70.7):

see separate sheet

Re Item V

**Reasoned statement with regard to novelty, inventive step or industrial applicability;
citations and explanations supporting such statement**

1. Reference is made to the following documents:

D1: WO-A-03069285

D2: WO-A-0023772

2. NOVELTY

2.1 Document D1 (or D2), which are considered the most relevant state of the art, disclose an integrated item batching and information handling system for producing batches of items, said system comprising:

- a process flow line with item batching means arranged between an item intake and at least one batch receptacle,
- a computer,
- first sensing means capable of transmitting electronic signal to said computer for establishing a first set of data representing characteristics of items entering the intake, and
- second sensing means capable of transmitting electronic signal to said computer for establishing data representing characteristics of batches from at least one batch receptacle,

wherein said computer receives said first set of data from said first sensing means and is adapted to generate a second set of data representing the characteristic of expected items entering the intake, and is further adapted to generate a third set of data representing the characteristics of expected batches from said expected items, and receives a fourth set of data from the second sensing means representing the characteristics of the actual batches.

2.2 The subject-matter of claim 1 differs in that the computer is adapted to generate a fifth set of data representing characteristics of a set of imaginary items, and corresponding conditions of batches expected from a theoretically ideal batching of said fifth set of data, furthermore, based on said sets of data, said information handling system presents the result for batches on demand and recommends the optimal one to the operator or controls

the batching system automatically.

2.3 Therefore the subject-matter of claim 1 is new and meets the requirements of Art. 33(2) PCT.

2.4 The same arguments apply to the corresponding method claim 16 which also meets the requirements of Art. 33(2) PCT.

2.5 Claims 2-15, 17-21 are dependent claims and thus meet the requirements of Art. 33(2) PCT.

3. INVENTIVE STEP

3.1 Document D1 uses the weight of partial batches to correct accumulated errors in the sum of weighted items and document D2 estimates statistical information about weight distribution along with information gathered during the batching process to calculate the ongoing efficiency and concurrently simulate the batching and suggests changes thereof. In contrast the subject-matter of claim 1 teaches the use of imaginary data sets based on historical data to simulate the batching process for generate information to aid the operator.

The skilled person, starting from D2 (or D1) and taking in account the skilled person's technical knowledge, would not provide a system as claimed in claim 1 as neither D1 nor D2 give an indication to do so.

3.2 Therefore the system claim 1 as well as the method claim 16 are not known or obvious from the prior art. Thus claim 1 and 16 are inventive.

4. INDUSTRIAL APPLICABILITY

4.1 The subject-matter of the above mentioned claims is considered as industrially applicable and these claims therefore fulfil the requirements of Art. 33(4) PCT.

**INTERNATIONAL PRELIMINARY
REPORT ON PATENTABILITY
(SEPARATE SHEET)**

International application No.

PCT/IS2004/000019

SIMULATION OF CONDITIONS IN A BATCHING PROCESS

Introduction

The present invention relates to a method and an apparatus for batching items of non-uniform weight into batches fulfilling certain weight criteria. The items are conveyed
5 across a scale registering the weight of each item individually, and subsequently, the items are combined into batches, e.g. based on statistical methods for obtaining minimum overweight or underweight in relation to the weight criteria. In particular, the invention relates to a method of analyzing process deviations in a batching process e.g. to detect faults in a batching system or in order to improve a batching process
10 flow, e.g. by re-organizing the order in which the products are processed. A typical application utilizing the present invention would measure a characteristic of items in the process and visually present the characteristics of these items along with the results of the batching process to an operator in a way so that the batching process may be improved. A more sophisticated application of the present invention would
15 include a simulation of the batching process to accurately predict the results for the pack-sizes on demand and recommend the optimal ones to the operator.

Background of the invention

In various industries, items are sold in batches satisfying various constraints. As an example, items of non-uniform size, shape or weight, e.g. food items such as meat,
20 fish, fruit and vegetables, are typically handled and delivered to customers in batches having a substantially uniform size, shape and weight. Typically, a batch of items must fulfill requirements defined by a contract between a delivering and a receiving part, and most often, minimum weight of the batch is a key issue. Normally, the part of the batch that exceeds the minimum weight is considered by the delivering part as a loss
25 and is often referred to as "giveaway", "overweight" or "overpack".

Typically, batches are formed by weighing the items individually, e.g. as they are moved by a conveyor system across a dynamic scale. In a computer system, the weight of each item is compared with weights of a plurality of receptacles, e.g. bins wherein batches are formed. Often, the computer system uses statistical algorithms
30 for assigning specific items to specific bins under consideration of required minimum weight of the batch and a desire not to produce batches with more overweight, i.e. giveaway, than required under the present conditions, i.e. given the weights of the items and the required minimum weight of the batches.

Evidently, there is a correlation between the amount of giveaway, the required minimum weight of the batches, and the weight distribution of the items being batched. In general, the larger the items are and the smaller the batches are, the more giveaway is expected.

- 5 Existing systems for batching items, e.g. conveyor systems for continuous batching of food items, are sometimes provided with a computer system, which is capable of registering certain process parameters, e.g. the batching throughput, e.g. determined in weight units or determined in numbers of pieces per time unit. It is, however, very difficult even for skilled operators to evaluate the performance of the system. As an
- 10 example, an operator may be satisfied by knowing that a large number of batches are formed within a certain time unit, while he never realizes that the amount of giveaway or the amount of batches with underweight is large, and even if control weighing of the batches reveals the truth, the complex nature of the batching process makes it difficult to determine the reason for the large number of batches with overweight or
- 15 underweight, neither to say if the situation is better or worse than expected. One reason for an undesirable result could be that the weight distribution of the items is not suitable for the batch or pack size being processed and another reason could be that a scale is out of order. In the existing systems for batching, it is therefore difficult to optimize the batching process, e.g. with the objective to minimize giveaway.

20 **Description of the invention**

It is an object of a preferred embodiment of the present invention to enable better control of a batching process. Accordingly, the present invention, in a first aspect, provides an integrated item batching and information handling system for producing batches of items, said system comprising:

- 25
- a process flow line with item batching means arranged between an item intake and at least one batch receptacle,
 - first sensing means for establishing first set of data representing characteristics of items entering the intake, and
 - a computer adapted, for a given batching principle to:

- generate a second set of data representing characteristics of a first set of data, a reference set of items of a type similar to the items entering the intake, and corresponding characteristics expected for batches of the first set of items.

5 During operation, the second set of data may be provided to an operator of the batching system for visualizing the characteristics that could be expected for batches batched from the items, i.e. as a reference for the actually ongoing batching. Accordingly, the operator is supported when determining the conditions of the system and the process of batching the items, and the operator has the opportunity to
10 interfere, e.g. when the second set of data deviates a lot from the results achieved in the system, i.e. the characteristics of the batches obtained during batching of the items.

The items could e.g. be food items of non-homogeneous size, shape, color, weight etc.

The process flow line could be a conveyor based flow line wherein items arrive, e.g.
15 from a previous process line, at a scale or similar sensor for determining a characteristic feature of the product. From the sensor, the item is conveyed towards a batching system comprising a plurality of batch receptacles with corresponding rejecting arms each being arranged to reject items from the conveyor to a receptacle. The first sensing means could be adapted to sense the color, size, shape, weight etc.
20 of the items. As an example, the sensing means could be a scale, e.g. an electronic scale or weighing machine capable of transmitting an electronic signal representative of the weight of the receptacle, e.g. a dynamic scale capable of sensing the weight of the items, while they are conveyed across the scale, or the sensor could comprise a vision system for detecting size or shape of an item.

25 The generation of the second set of data may take place simultaneously with the batching of items and the data may be regularly updated. Usually, the second set of data would be generated as early in the process as possible. The second set of data may also be a data set, which is generated only once, e.g. in connection with installation of the system. The characteristics of the items could relate to the above
30 mentioned sensing variables, i.e. a color, a quality parameter or to the weight, size or shape of the item. Correspondingly, the characteristics of the batch could relate to a color, a quality parameter, the total weight of the batch, the size or shape of the batch

or to an overweight or an underweight of the batch. As an example, the second set of data can be generated, e.g. by the computer prior to installation of the system, or as a part of an installation procedure or during the first days of operation of the plant. The second set of data could comprise an average value of the weights of items, which are expected to arrive and an average value of overweight, which must be expected for given values of batch weights. The second set of data may be obtained, e.g. from historical data describing previous batching of similar items.

In order to compare the characteristics of actually entering items i.e. the first set of data with the second set of data, the computer could receive the data from the first sensing means and generate a first set of data representing characteristics of items entering the intake. Based on the received data i.e. the first set of data, the computer may calculate expected conditions of batches, i.e. the third set of data, resulting from batching of the items entering the intake. The calculation could be based on an average item weight, a number of batch receptacles and a desired end weight of the receptacles, and may return an average overweight of the receptacles.

To compare the characteristics of actually formed batches, e.g. for controlling the batching process, the system may further have second sensing means for establishing data representing characteristics of the at least one batch receptacle. Data, which the computer receives from the second sensing means, can be incorporated in a fourth set of data representing actual conditions of batches being batched. The second sensing means could sense the color, size, shape, weight etc. of the batch receptacles while they are being filled with items. As an example, the sensing means could be a scale, e.g. an electronic scale or weighing machine, capable of transmitting an electronic signal representative of the weight of the receptacle, or the sensing means may comprise a vision system for detecting size and/or shape of a batch.

The computer could be a regular PC or any similar electronic processor capable of processing data. As an example, the computer may comprise a central processing unit arranged to receive data from the first and the second sensing means. The computer may have additional processing units connected between at least one of the sensing means and the central processing unit. As an example, the first and/or the second sensing means may each have a processing unit capable of processing the data, e.g. data relating to the weight of the items or batch receptacles, and to process this data, e.g. to return a mean value or a standard deviation of the sensed characteristic.

An operator of the system could be allowed to key in data, e.g. representing characteristics of items, which are expected to be received in the future i.e. the second set of data. The system may have a data storage and data entering means allowing entering of data sets into the data storage means. In one embodiment of the invention, the computer can generate a fifth set of data representing imaginary data, e.g. non-existing items, and corresponding characteristics of batches expected for a theoretically ideal batching of the fifth set of items. The fifth set of data can be used by an operator of the system to determine how far away a presently ongoing batching process is from a theoretically optimal batching process, e.g. a batching process, wherein the equipment is assumed to function faultless, i.e. a situation, wherein the scales determines the weights exactly, wherein a rejecting arm never fails to reject an item into a receptacle, and wherein the characteristics of the items are expected to be within a certain statistical distribution.

Preferably, the system is provided with a conveyor for conveying the items from the intake and across the first sensor towards batching means, e.g. comprising rejecting arms, and into batch receptacles. As an example, the conveyor may be formed by an endless belt, an overhead connected line of shackles, or a plurality of adjacent rolls. Depending upon the sensing means, e.g. by incorporating a dynamic scale for weighing the items, the computer may generate and compare data sets during conveying of items across the scale.

In order to provide the operator of the system with easily understandable data, the computer may generate a correlation insignia representing a correlation between at least two of the data sets, e.g. between the second and first data set or between the second and fourth data set. As an example, the second data set may comprise historical data corresponding to the average weight of items entering the system and corresponding overweight of batches comprising these items. The correlation insignia could represent a correlation between this second data set and data representing average weight of presently batched items, i.e. the fourth data set, and corresponding overweight of the presently formed batches. As an example, the insignia could be defined as data from the second set of data divided with data from the third set to data, vise versa. Alternatively, the insignia could represent data from the second set of data minus data from the first set of data, vise versa.

5

15

The second and the third sets of data may represent one of:

20

a standard deviation of the first set of items,

and one of:

a corresponding average overweight expected for batches of the first set of items, and

25

Correspondingly, the first and the fourth sets of data may represent one of:

an average weight of the first set of items, and

a standard deviation of the first set of items.

In a preferred embodiment, the system can recalculate expected characteristics of batches based on user input and/or acquired data. As an example, the user can enter characteristics of items, e.g. an average weight of items, into the system, which then
5 calculates expected characteristics of the batches, e.g. an average overweight. The calculation could be based on empirical data or an analytically determined mathematical function, i.e. the procedure could create a random set of items based on the characteristics entered (e.g. average weight, standard deviation and normal distribution), and then using the same algorithm to batch the created set of numbers,
10 i.e. the fifth set of data, as being used in the real world. The result is the expected characteristics of the batches.

According to a second aspect, the present invention relates to a method of analysing process data in a batching process of an Integrated Item batching and Information handling system of the kind comprising a process flow line with item batching means
15 arranged between an item intake and at least one batch receptacle, and first sensing means for establishing first set of data representing characteristics of items entering the intake, said method comprising the steps of

- conveying items between an item intake and at least one batch receptacle in an item processing line,
- 20 - establishing first set of data representing characteristics of items entering the intake, and
- generating a second set of data representing conditions of a first set of items, and corresponding conditions expected for batches of the first set of items.

In particular, the method is concerned with analysing weight data of a food processing
25 equipment in accordance with any of the features described for the system according to the first aspect of the invention.

Detailed description of the invention

In the following, a preferred embodiment of the invention will be referred to in the term of a SmartPack system. The system will be described in further details with reference to the drawing in which:

5 Fig. 1 shows an Integrated Item batching and information handling system according to the invention,

Fig. 2 shows a system overview,

Fig. 3 shows an example of the real-time over-pack graphs,

Fig. 4 shows an example of real-time monitoring graphs,

10 Fig. 5 shows an example of real-time process graphs, and

Figs. 6-12 show various examples of reports and graphs.

Fig. 1 shows an Integrated Item batching and information handling system for producing batches of items. The system comprises a batching process flow line with a conveyor 1 conveying items 9, 11 in the direction of the arrow 2 from a dynamic scale
15 or similar sensing means 10 towards batching means comprising rejecting arms 3 arranged along the conveyor for rejecting the items into the batch receptacles 4. As shown in Fig. 1, two items have been rejected from the conveyor into the receptacle with numeral 12. The weight of the receptacle is determined by a second sensing means in form of a static scale. The scale transmits weight related data via the
20 connection 5 to the computer 6. The computer further receives weight related data from the first sensing means via the connection 7 and controls the rejecting arms via the connection 8. The computer is capable of generating sets of data representing characteristics of sets of items entering the intake, and corresponding characteristics expected for batches of the sets of items, and capable of processing the data and
25 visualizing the data.

The SmartPack system monitors the evolution of overweight in batches – in the following text referred to as packs. It will enable an operator of the system to monitor and decide how to minimize overweight in packs that are currently running. An

operator can choose to monitor the packs that are most important by value and therefore increase the pack margin.

Fig. 2 shows a system overview wherein a client computer system 20 of a batching system and a client computer system 21 of a check weight are connected to a server computer system 22 for passing data relating to the weight or relating to similar characteristics of items or batches via an Ethernet connection 23. Three client computers systems 24-26 are connected and provide operators with support in planning the batching process or support in detecting system faults. SmartPack provides two kinds of information, i.e. real-time graphs monitoring overpack and production, and historical reports providing different aspects of analyzing overpack. The option of simulating the theoretical baseline for a production is available. The difference between current overpack and the theoretical simulated overpack is the major opportunity for possible overpack reduction.

The user interface of the client computer systems 24-26 is in accordance with a standard architecture of the general computer interfaces of the batching system. The software has two different access levels, Operator and Administrator level. The SmartPack system has no adjustment or setup tables but only reports for monitoring, both historical and real-time.

An operator level of the user interface is intended for a production supervisor. It visualizes of the following real time graphs.

- **Overpack** focusing on the total overweight of all packs being created and the possibility of identifying pack(s) that is significantly out of order.
 - **Monitoring** focusing on the process of creating packs from pieces.
 - **Process** focusing on the steps from packing to check-weighing.
- Overpack shows two different real-time graphs. It has selection box for current packs in production and the user can select pack to be monitored. Fig. 3 shows example of the overpack monitoring graphs.

- **Overpack** showing overpack in percentage or in weight/pack.

- **Total overpack** showing summed overpack in percentage for all packs being created.
- Monitoring shows three different real-time graphs. It has selection box for current packs in production and the user can select pack to be monitored.
5 Figure 4 shows example of the overpack monitoring graphs. **Overpack** showing overpack in % or weight/pack.
- **Input** showing average weight of pieces in weight/piece or pieces/pack.
- **Throughput** showing production rate of different packs in weight/hour or packs/min.

10 Fig. 5 shows a graphical view of data sets for an overpack process in three different real-time graphs. One selection box for current packs in production is for all the graphs. The user can select pack to be shown. Only one pack can be shown at a given time.

- **Overpack** showing overpack both at the creation of the packs and at check-weighing in percentage or weight/pack.
15
- **Check-weighing** showing rate of underweight packs, overweight packs and acceptable packs.
- **Throughput** showing production rate of the packs at the creation of the pack, into check-weighing, and from check-weighing in weight/hour or packs/min.

20 The operator of the system can print out various reports selected from a report menu.

In the following, a number of reports will be described in further detail.

Fig. 6 shows a report called Production list. Production list helps the production manager to analyze the weights and rejects from the point of receiving individual pieces to the point delivering accepted trays. The report lists the following values for
25 each product.

- Total input weight into the packing system
- Total final weight accepted by the a person assigned to check the weights, i.e. a check-weigher
- Weight share representing the percentage of final weight for this product of total production final weight
- Total reject showing percentage difference between input weight and final weight
- Batch reject representing reject (under weights and over weights) at the Check-Bln grader
- Final reject representing reject at the check-weigher

Fig. 7 shows a report called Overpack list. Overpack list gives a summary of net weight packs produced. The report lists the following values for each product.

- Total boxes produced of this product
- Total packs produced of this product
- Total weight of product produced
- Total overpack of product produced
- Nominal weight of product (net weight)
- Overpack on average for each pack produced
- Overpack percentage for each pack
- Pieces per pack on average

Fig. 8 shows a report/graph called Overpack correlation. Overpack correlation plots all process periods for the selected product on a scatter graph. The x-axis represents average pieces per pack during the process period. The y-axis represents overpack percentage for the process period. Yellow dot is the current process period (still open), red dots are process periods completed today, and green dots are process periods from yesterday or older. The red line is the best fitted line through all the dots plotted.

Fig. 9 shows a report/bar graph called Throughput history. Each bar represents the production volume for a given time period (day, week, month). This report is used for tracking the volume of production for products.

Fig. 10 shows a report/graph called Overpack history. Each dot represents the overpack during a given time period (day, week, month). This report shows the trend of overpack for products.

Fig 11 shows a report called Overpack comparison. This report is used for comparing the overpack on the Check-Bin grader and the overpack on the Check-weigher. The report lists the following values for each product.

- Batch overpack, both weight and percentage. This is the overpack from the Check-Bin grader, where pieces are collected into fixed weight batches.
- Final overpack, both weight and percentage. This is the overpack from the Check-weigher for accepted packs
- Difference between final and batch overpack, both weight and percentage.

Fig. 12 shows a report called Product by period. For a given product, this shows all process periods that have been created. This helps to pick out specific process periods with exceptionally good or bad results to analyze further in other MPS modules. The report lists the following values for each product.

- Process period number.
- Process unit, the Check-Bin grader or Check-weigher used.

- Date and time for the start and end of process period
- Batch/Pack count for the process period
- Final weight for the process period
- Average overpack during the process period

CLAIMS

1. An Integrated item batching and information handling system for producing batches of items, said system comprising:

5 – a process flow line with item batching means arranged between an item intake and at least one batch receptacle,

 – a computer,

 – first sensing means capable of transmitting electronic signal to said computer for establishing a first set of data representing characteristics of items entering the intake, and

10 – second sensing means capable of transmitting electronic signal to said computer for establishing data representing characteristics of batches from at least one batch receptacle,

 wherein said computer receives said first set of data from said first sensing means and is adapted to generate a second set of data representing the characteristic of expected
15 items entering the intake, and is further adapted to generate a third set of data representing the characteristics of expected batches from said expected items, and receives a fourth set of data from the second sensing means representing the characteristics of the actual batches, characterized in that the computer is adapted to generate a fifth set of data representing characteristics of a set of imaginary items,
20 and corresponding conditions of batches expected from a theoretically ideal batching of said fifth set of data, furthermore, based on said sets of data, said information handling system presents the result for batches on demand and recommends the optimal one to the operator or controls the batching system automatically.

25 2. A system according to claim 1, wherein the computer comprises one central processing unit receiving data from the first and the second sensing means.

3. A system according to any of the preceding claims wherein the computer comprises additional processing units connected between at least one of the sensing means and the central processing unit.

4. A system according to any of the preceding claims, further comprising a data storage means and data entering means allowing entering of data sets into the data storage means.

5 5. A system according to any of the preceding claims, comprising a conveyer for conveying the items from the intake passed the first sensor and the batching means to the at least one batch receptacle.

6. A system according to claim 5, wherein the computer is adapted to generate and compare data sets during the conveying of items.

10 7. A system according to any of the preceding claims, wherein at least one of the first and second sensing means comprises a scale for determining data representative of a weight of an item or batch receptacle.

8. A system according to any of the preceding claims,, wherein the computer is adapted generate a correlation between two of the first, second, third and fourth sets of data.

15 9. A system according to any of the preceding claims, wherein the computer is adapted to visualize at least one of the first, the second, the third and the fourth sets of data graphically on a screen.

20 10. A system according to any of the preceding claims, wherein the computer is adapted to visualize a correlation between two or more of the first, second, third and fourth sets of data.

11. A system according to claims 9, wherein the computer is adapted to visualize more than one data set or more than one correlation in a single screen image.

12. A system according to any of the preceding claims, wherein at least one of the second and the third sets of data represent one of:

25 an average weight of the first set of items, and

a standard deviation of the first set of items,

and one of:

a corresponding average overweight expected for batches of the first set of items, and

a number of batches expected to have an underweight.

- 5 13. A system according to any of the preceding claims, wherein at least one of the first and fourth sets of data represents one of:

an average weight of the first set of items, and

a standard deviation of the first set of items.

- 10 14. A system according to any of the preceding claims, wherein the computer system comprises data input means allowing a user to enter data into at least one of the second, third and fourth sets of data. 15. A system according to any of the preceding claims, wherein the computer system is adapted to recalculate expected conditions of batches based on the second and third sets of data based on a user request.

- 15 16. A method of analyzing process data in a batching process of an integrated item batching and information handling system of the kind comprising a process flow line with item batching means arranged between an item intake and at least one batch receptacle, first sensing means for establishing data representing characteristics of items entering the intake, and second sensing means for establishing data representing the characteristics of the batches, said method comprising the steps of
- 20 – conveying items between an item intake and at least one batch receptacle in an item processing line,
- establishing first set of data representing characteristics of items entering the intake, and
- 25 – generating a second set of data representing characteristics of expected items entering the intake, and

- generate a third set of data, representing the characteristics of expected batches from said expected items, and
- receiving data from said second sensor, and establish a fourth set of data, representing the actual conditions of batches, and
- 5 - generate a fifth set of data of imaginary items,
- calculate theoretically ideal batches,
- wherein said theoretically ideal batches are calculated from said imaginary items contained in said fifth set of data.

10 17. A method according to claim 16, further comprising generating a correlation between two of the second, third, fourth and fifth sets of data.

18. A method according to any of claims 16-17, further comprising visualising at least one of the second, the third, the fourth and the fifth sets of data graphically on a screen.

15 19. A method according to any of claims 16-18, further comprising visualising a correlation between two or more of the second, third, fourth and fifth sets of data.

20. A method according to claims 17-18, wherein more than one data set or more than one correlation is visualized in a single screen image.

21. A method according to any of claims 17-20, wherein the data represents weights of the items and batches.